


# Actuator

02-  
198.011



<https://www.eao.com/p/02-198.011>

Your product:



# 02-198.011

## Actuator

### PRODUCT RANGE

**Product Status:** Not Recommended for new design

### FRONT

**Front dimension:** 36 mm x 24 mm

**Front form:** Rectangular

**Front bezel colour:** Black

**Front bezel material:** Plastic

### MOUNTING

**Design:** Flush

**Mounting cut-out:** 21.2 mm x 29.2 mm

**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

<b>Switching voltage and switching current:</b>	according to UL	
	250 VAC, 10 A	
	according to IEC 60947-5-1	
	AC-12: 400 V, 10 A	AC-15: 400 V, 6 A
	AC-15: 250 V, 8 A	DC-13: 110 V, 0.4 A
	DC-13: 60 V, 1 A	DC-13: 24 V, 3 A
<b>Contacts:</b>	2 C	
<b>Rated insulation voltage Ui:</b>	400 VAC/440 VDC according to IEC 60947-5-1	
<b>Switching rating:</b>	400 V @ 10 A	
<b>Standards:</b>	The switches comply with the "Standards for low-voltage switching devices" EN IEC 60947-5-1	
<b>Thermal current Ith:</b>	10 A	

## MECHANICAL CHARACTERISTICS

<b>Terminal:</b>	Screw terminal
<b>Contact material:</b>	Silver
<b>Switching action:</b>	Rest (a) - Momentary
<b>Switching system:</b>	Snap-action switching element
<b>Switching system:</b>	1 or 2 self-cleaning snap action switching elements. 1 or 2 double-throw contacts.
<b>Switching positions:</b>	2 positions
<b>Switching angle:</b>	90° right
<b>Mechanical lifetime:</b>	2 Mil. cycles of operation
<b>Operating force:</b>	6 ... 12 N
<b>Tightening torque:</b>	Fixing nut max. 0.2 Nm, Screw terminal 0.8 Nm
<b>Terminal details 1:</b>	Max. wire cross-section 2 mm x 2.5 mm <sup>2</sup> Max. wire cross-section of stranded cable 2 x 1.5 mm <sup>2</sup>
<b>Weight:</b>	0.055 kg

## AMBIENT CONDITION

<b>IP Protection:</b>	IP40 front side, IP65 with spray cover, according to IEC 60529
<b>Operating temperature:</b>	- 25 °C ... + 55 °C, mounted as a block, make sure the heat can escape freely
<b>Storage temperature:</b>	- 30 °C ... + 85 °C
<b>Shock resistance:</b>	15 g for 11 ms, according to IEC 60068-2-27
<b>Vibration resistance:</b>	10 g at 10 Hz...2000 Hz, amplitude 1.0 mm, according to IEC 60068-2-6

## CERTIFICATE

### Approbations:

CB (IEC 60947-5-1), CENELEC CCA-NTR (EN 60947-5-1), CSA, DNV, SEV, UL

### Conformities:

CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

### REACH:

REACH compliant

### RoHS:

RoHS compliant

## OTHER


### Short Description:

Actuator, 21.2 mm x 29.2 mm, 36 mm x 24 mm, Rectangular, Black, Plastic, 2 C, Rest (a) - Momentary, Screw terminal


### Product attributes:

A = lockable, actuated; can be used with protective cover Part No. 22-925


### Switching positions:



### Wiring diagrams:



### Mounting cut-outs:



### Dimension drawings:

