

Actuator

45-

2131.1110.000





Your product:



45-2131.1110.000 Actuator

FRONT

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Black

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

Lens type: Level with front bezel


MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime: 500 000 cycles of operation

Weight: 0.019 kg AMBIENT CONDITION IP front protection: IP66, IP67, IP69K	
IP front protection: IP66, IP67, IP69K	
IP front protection: IP66, IP67, IP69K	
Operating temperature: - 25 °C + 70 °C	
Storage temperature: $-40 ^{\circ}\text{C} \dots + 80 ^{\circ}\text{C}$	
Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE	
REACH: REACH compliant	
RoHS: RoHS compliant	
OTHER	
Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Non illuminated, Black, Plastic, op Round, Black, Plastic, Momentary, IP66, IP67, IP69K	aque,
Housing colour: Black	
Housing material: Plastic	
Wiring diagrams:	
Mounting cut-outs:	



Dimension drawings:

