

# Actuator

45-2131.2110.000







## 45-2131.2110.000 Actuator

	_	_		-
ь.	к	()	N	

Front dimension: Ø 29,5 mm

Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Front form:

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Black

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

**Lens optics:** opaque

**Lens type:** Level with front bezel


#### **MECHANICAL CHARACTERISTICS**

**Switching action:** Momentary

Switching system: Slow-make switching element

**Mechanical lifetime:** 500 000 cycles of operation

Operating frequency:	Max. 3 600/h		
Weight:	0.04 kg		
AMBIENT CONDITION			
IP front protection:	IP66, IP67, IP69K		
Operating temperature:	– 25 °C + 70 °C		
Storage temperature:	– 40 °C + 80 °C		
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms		
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g		
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, $\varnothing$ 22.3 mm, $\varnothing$ 29,5 mm, Flush, Non illuminated, Black, Plastic, opaque, Round, Silver, Metal, Momentary, IP66, IP67, IP69K		
Housing colour:	Silver		
Housing material:	Metal		
Wiring diagrams:			
Mounting cut-outs:			



### Dimension drawings:

