

Actuator

45-2131.2140.000







45-2131.2140.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: \varnothing 29,5 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Yellow

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

Lens type: Level with front bezel


MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime: 500 000 cycles of operation

Operating frequency:	Max. 3 600/h		
Weight:	0.04 kg		
AMBIENT CONDITION			
IP front protection:	IP66, IP67, IP69K		
Operating temperature:	– 25 °C + 70 °C		
Storage temperature:	– 40 °C + 80 °C		
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms		
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g		
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Non illuminated, Yellow, Plastic, opaque, Round, Silver, Metal, Momentary, IP66, IP67, IP69K		
Housing colour:	Silver		
Housing material:	Metal		
Wiring diagrams:			
Mounting cut-outs:			



Dimension drawings:

