

# Actuator

45-  
2131.2350.000



<https://eao.com/p/45-2131.2350.000>

Your product:

---



## 45-2131.2350.000 Actuator

### FRONT

|                              |           |
|------------------------------|-----------|
| <b>Front dimension:</b>      | Ø 29,5 mm |
| <b>Front form:</b>           | round     |
| <b>Front bezel colour:</b>   | Silver    |
| <b>Front bezel material:</b> | Metal     |

### MOUNTING

|                          |                |
|--------------------------|----------------|
| <b>Design:</b>           | raised         |
| <b>Mounting cut-out:</b> | Ø 22.3 mm      |
| <b>Mounting type:</b>    | Panel mounting |

### OPERATING-/INDICATION PART

|                           |                  |
|---------------------------|------------------|
| <b>Lens colour:</b>       | Green            |
| <b>Lens material:</b>     | Plastic          |
| <b>Lens illumination:</b> | non illuminative |
| <b>Lens shape:</b>        | flush            |
| <b>Lens optics:</b>       | opaque           |

### MECHANICAL CHARACTERISTIC

|                             |                             |
|-----------------------------|-----------------------------|
| <b>Switching action:</b>    | Momentary                   |
| <b>Switching system:</b>    | Slow-make switching element |
| <b>Mechanical lifetime:</b> | 500 000 cycles of operation |
| <b>Operating frequency:</b> | Max. 3 600/h                |

**Weight:** 0.049 kg

### **AMBIENT CONDITION**

**IP front protection:** IP66, IP67, IP69K

**Operating temperature:** – 25 °C ... + 70 °C

**Storage temperature:** – 40 °C ... + 80 °C

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 20 ... 500 Hz: 5 g

**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

### **CERTIFICATE**

**REACH:** REACH compliant

**RoHS:** RoHS compliant


### **OTHER**

**Short Description:** Actuator, Ø 22.3 mm, Ø 29,5 mm, flush, non illuminative, Green, Plastic, opaque, round, Silver, Metal, Momentary, IP66, IP67, IP69K

**Housing colour:** Silver

**Housing material:** Metal

**Wiring diagrams:**



**Mounting cut-outs:**



Dimension drawings:

