

Actuator

45-
2131.4F10.000



<https://eao.com/p/45-2131.4F10.000>

Your product:



45-2131.4F10.000 Actuator

FRONT

| | |
|------------------------------|-----------|
| Front dimension: | Ø 38 mm |
| Front form: | round |
| Front bezel colour: | Sand grey |
| Front bezel material: | Metal |

MOUNTING

| | |
|--------------------------|----------------|
| Design: | flush |
| Mounting cut-out: | Ø 30.5 mm |
| Mounting type: | Panel mounting |

OPERATING-/INDICATION PART

| | |
|---------------------------|------------------|
| Lens colour: | Black |
| Lens material: | Plastic |
| Lens illumination: | non illuminative |
| Lens shape: | flush |
| Lens optics: | opaque |

MECHANICAL CHARACTERISTIC

| | |
|-----------------------------|-----------------------------|
| Switching action: | Momentary |
| Switching system: | Slow-make switching element |
| Mechanical lifetime: | 500 000 cycles of operation |
| Operating frequency: | Max. 3 600/h |

Weight: 0.074 kg

AMBIENT CONDITION

IP front protection: IP66, IP67, IP69K

Operating temperature: – 25 °C ... + 70 °C

Storage temperature: – 40 °C ... + 80 °C

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 20 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER


Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, flush, non illuminative, Black, Plastic, opaque, round, Sand grey, Metal, Momentary, IP66, IP67, IP69K

Housing colour: Silver

Housing material: Metal

Hints: Front panel thickness 1 ... 6 mm

Wiring diagrams:



Dimension drawings:

