

Actuator

45-
2131.4F60.000



<https://www.eao.com/p/45-2131.4F60.000>

Your product:



45-2131.4F60.000 Actuator

FRONT

Front dimension:	Ø 38 mm
Front form:	Round
Front bezel colour:	Sand grey
Front bezel material:	Metal

MOUNTING

Design:	Flush
Mounting cut-out:	Ø 30.5 mm
Mounting type:	Panel mounting

OPERATING-/INDICATION PART

Lens colour:	Blue
Lens material:	Plastic
Lens illumination:	Non illuminated
Lens shape:	Flush
Lens optics:	opaque

ELECTRICAL CHARACTERISTICS

Switching rating:

MECHANICAL CHARACTERISTIC

Switching action: Momentary

Switching system: Slow-make switching element
Mechanical lifetime: 500 000 cycles of operation
Operating frequency: Max. 3 600/h
Weight: 0.074 kg

AMBIENT CONDITION


IP front protection: IP66, IP67, IP69K
Operating temperature: – 25 °C ... + 70 °C
Storage temperature: – 40 °C ... + 80 °C
Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance: According to IEC 60068-2-6: 20 ... 500 Hz: 5 g
Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant
RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Blue, Plastic, opaque, Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K
Housing colour: Silver
Housing material: Metal
Hints: Front panel thickness 1 ... 6 mm
Wiring diagrams:



Dimension drawings:

