

# Actuator

45-  
2134.2120.000



<https://www.eao.com/p/45-2134.2120.000>

Your product:

---



## 45-2134.2120.000 Actuator

### FRONT

|                              |           |
|------------------------------|-----------|
| <b>Front dimension:</b>      | Ø 29,5 mm |
| <b>Front form:</b>           | Round     |
| <b>Front bezel colour:</b>   | Silver    |
| <b>Front bezel material:</b> | Metal     |

### MOUNTING

|                          |                |
|--------------------------|----------------|
| <b>Design:</b>           | Raised         |
| <b>Mounting cut-out:</b> | Ø 22.3 mm      |
| <b>Mounting type:</b>    | Panel mounting |

### OPERATING-/INDICATION PART

|                           |                        |
|---------------------------|------------------------|
| <b>Lens colour:</b>       | Red                    |
| <b>Lens material:</b>     | Plastic                |
| <b>Lens illumination:</b> | Non illuminated        |
| <b>Lens shape:</b>        | Flush                  |
| <b>Lens optics:</b>       | opaque                 |
| <b>Lens type:</b>         | Level with front bezel |

### ELECTRICAL CHARACTERISTICS

**Switching rating:**

### MECHANICAL CHARACTERISTIC

**Switching action:** Maintained  
**Switching system:** Slow-make switching element  
**Mechanical lifetime:** 10 Mil. cycles of operation  
**Weight:** 0.036 kg

### AMBIENT CONDITION


**IP front protection:** IP66, IP67, IP69K  
**Operating temperature:** - 25 °C ... + 70 °C  
**Storage temperature:** - 40 °C ... + 80 °C  
**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  
**Vibration resistance:** According to IEC 60068-2-6: 20 ... 500 Hz: 5 g  
**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

### CERTIFICATE

**REACH:** REACH compliant  
**RoHS:** RoHS compliant

### OTHER

**Short Description:** Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Non illuminated, Red, Plastic, opaque, Round, Silver, Metal, Maintained, IP66, IP67, IP69K  
**Housing colour:** Silver  
**Housing material:** Metal  
**Hints:** Push to unlatch  
**Wiring diagrams:**



**Mounting cut-outs:**



Dimension drawings:

