

# Actuator

45-2530.2920.000







## 45-2530.2920.000 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension:  $\emptyset$  40 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

**Lens optics:** opaque

## **MECHANICAL CHARACTERISTICS**


Switching action: Maintained

**Switching system:** Slow-make switching element

Release type: Pull unlock

**Mechanical lifetime:** 500 000 cycles of operation

Operating frequency:	Max. 1 800/h	
Weight:	0.063 kg	
AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 22.3 mm, Ø 40 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Silver, Metal, Maintained, IP66, IP67, IP69K, Pull unlock	
Housing colour:	Silver	
Housing material:	Metal	
Wiring diagrams:		
	_~-	
Mounting cut-outs:		



## Dimension drawings:

