

# Actuator

45-2531.2950.000







## 45-2531.2950.000 Actuator

## **FRONT**

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

### **OPERATING-/INDICATION PART**

Lens colour: Green

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

**Lens optics:** opaque

## **MECHANICAL CHARACTERISTICS**


**Switching action:** Momentary

Switching system: Slow-make switching element

**Mechanical lifetime:** 10 Mil. cycles of operation

**Operating frequency:** Max. 3 600/h

Weight:	0.049 kg
AMBIENT CONDITION	
IP front protection:	IP66, IP67, IP69K
Operating temperature:	– 25 °C + 70 °C
Storage temperature:	– 40 °C + 80 °C
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, $\varnothing$ 22.3 mm, $\varnothing$ 40 mm, Mushroom-head, Non illuminated, Green, Plastic, opaque, Round, Silver, Metal, Momentary, IP66, IP67, IP69K
Housing colour:	Silver
Housing material:	Metal
Wiring diagrams:	<b>E</b>
Mounting cut-outs:	



## Dimension drawings:

