

# Actuator

45-  
2630.29E0.000



<https://www.eao.com/p/45-2630.29E0.000>

Your product:

---



## 45-2630.29E0.000 Actuator

### FRONT

<b>Front dimension:</b>	Ø 40 mm
<b>Front form:</b>	Round
<b>Front bezel colour:</b>	Silver
<b>Front bezel material:</b>	Metal

### MOUNTING

<b>Design:</b>	Raised
<b>Mounting cut-out:</b>	Ø 22.3 mm
<b>Mounting type:</b>	Panel mounting

### OPERATING-/INDICATION PART

<b>Lens colour:</b>	Red
<b>Lens material:</b>	Plastic
<b>Lens illumination:</b>	Illuminated
<b>Lens shape:</b>	Mushroom-head
<b>Lens optics:</b>	transparent

### ELECTRICAL CHARACTERISTICS

**Switching rating:**

### MECHANICAL CHARACTERISTIC

**Switching action:** Maintained

**Switching system:** Slow-make switching element  
**Release type:** Pull unlock  
**Mechanical lifetime:** 500 000 cycles of operation  
**Operating frequency:** Max. 1 800/h  
**Weight:** 0.063 kg

#### **AMBIENT CONDITION**

**IP front protection:** IP66, IP67, IP69K  
**Operating temperature:** – 25 °C ... + 70 °C  
**Storage temperature:** – 40 °C ... + 80 °C  
**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  
**Vibration resistance:** According to IEC 60068-2-6: 20 ... 500 Hz: 5 g  
**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

#### **CERTIFICATE**

**REACH:** REACH compliant  
**RoHS:** RoHS compliant

#### **OTHER**

**Short Description:** Actuator, Ø 22.3 mm, Ø 40 mm, Mushroom-head, Illuminated, Red, Plastic, transparent, Round, Silver, Metal, Maintained, IP66, IP67, IP69K, Pull unlock

**Housing colour:** Silver

**Housing material:** Metal

**Wiring diagrams:**

**Mounting cut-outs:**

**Dimension drawings:**

