

Actuator

45-2816.2D90.003





https://www.eao.com/component/45-2816.2D90.00...



45-2816.2D90.003 Actuator

	_	_		-
ь.	к	()	N	

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever colour: White

Lever material: plastic

Lever shape: long

MECHANICAL CHARACTERISTICS

Switching action: Maintained - Rest - Momentary

Switching positions: 3 positions

Switching angle: 45° left / 45° right / -45° ... $+45^{\circ}$

Mechanical lifetime: 1 Mil. cycles of operation

Operating frequency: 1 800/h

Weight: 0.052 kg

AMBIENT CONDITION

IP front protection: IP66, IP67, IP69K

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER


Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, optional illuminative, White, long, Round, Silver,

Metal, Maintained - Rest - Momentary, IP66, IP67, IP69K

Housing material: Metal

Hints: External diameter of the long lever 44.8 mm


Switching positions:



Wiring diagrams:



Mounting cut-outs:



Dimension drawings:

