

# Actuator

45-  
290K.1000.116



<https://eao.com/p/45-290K.1000.116>

Your product:

---



## 45-290K.1000.116 Actuator

### FRONT

<b>Front dimension:</b>	Ø 29,5 mm
<b>Front form:</b>	round
<b>Front bezel colour:</b>	Black
<b>Front bezel material:</b>	Plastic

### MOUNTING

<b>Design:</b>	raised
<b>Mounting cut-out:</b>	Ø 22.3 mm
<b>Mounting type:</b>	Panel mounting

### MECHANICAL CHARACTERISTIC

<b>Switching action:</b>	Rest (a) - Momentary
<b>Switching positions:</b>	2 positions
<b>Switching angle:</b>	45° right
<b>Mechanical lifetime:</b>	1 Mio. cycles of operation
<b>Operating frequency:</b>	1 800/h
<b>Weight:</b>	0.054 kg

### AMBIENT CONDITION

<b>IP front protection:</b>	IP66, IP67, IP69K
<b>Operating temperature:</b>	- 25 °C ... + 70 °C
<b>Storage temperature:</b>	- 40 °C ... + 80 °C

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

### CERTIFICATE

**REACH:** REACH compliant

**RoHS:** RoHS compliant


### OTHER

**Short Description:** Actuator, Ø 22.3 mm, Ø 29,5 mm, round, Black, Plastic, Rest (a) - Momentary, IP66, IP67, IP69K

**Housing material:** Plastic

**Hints:** The standard lock: RONIS, T254

**Switching positions:**



**Wiring diagrams:**



**Mounting cut-outs:**



Dimension drawings:

