

Actuator

45-2D36.1A20.000







45-2D36.1A20.000 Actuator

E	D	0	N	п
г	п	v	14	

Front dimension: Ø 60 mm

Front form: round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: illuminative

Lens shape: mushroom-head

Lens optics: opaque

MECHANICAL CHARATERISTIC

Switching action: Maintained

Release type: Twist to unlock

Mechanical lifetime: 300 000 cycles of operation

Operating frequency: Max. 600/h

Weight: 0.05 kg

AMBIENT CONDITION

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 2 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 60 mm, mushroom-head, illuminative, Red, Plastic, opaque, round,

Black, Plastic, Maintained, Twist to unlock


Dimension: Ø 60 mm

Housing colour: Yellow


Housing material: Plastic

Hints: Application as per DIN EN ISO 13850 and EN 60204-1


Wiring diagrams:



Mounting cut-outs:



Dimension drawings:



Where to Buy

	Distributor	Quantity in Stock	
Newark	Newark	12 in stock	Buy 📜
DISTRELEC	Distrelec	10 in stock	Buy □
DigiKey	DigiKey	9 in stock	Buy □
tme.eu	TME	5 in stock	Buy □
Farnell	Farnell UK	5 in stock	Buy □

Show more $\,+\,$

Powered by oemsecrets.com