

# Actuator

45-  
2N39.2010.000



<https://eao.com/p/45-2N39.2010.000>

Your product:

---



## 45-2N39.2010.000 Actuator

### FRONT

<b>Front dimension:</b>	Ø 29,5 mm
<b>Front form:</b>	round
<b>Front bezel colour:</b>	Silver
<b>Front bezel material:</b>	Metal

### MOUNTING

<b>Design:</b>	raised
<b>Mounting cut-out:</b>	Ø 22.3 mm
<b>Mounting type:</b>	Panel mounting

### OPERATING-/INDICATION PART

<b>Lever colour:</b>	Black
<b>Lever material:</b>	plastic

### MECHANICAL CHARACTERISTIC

<b>Switching action:</b>	Momentary
<b>Mechanical lifetime:</b>	1 Mio. cycles of operation
<b>Operating frequency:</b>	1 800/h
<b>Weight:</b>	0.038 kg

### AMBIENT CONDITION

<b>IP front protection:</b>	IP66, IP67, IP69K
-----------------------------	-------------------


<b>Operating temperature:</b>	- 25 °C ... + 70 °C
<b>Storage temperature:</b>	- 40 °C ... + 80 °C
<b>Shock resistance:</b>	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
<b>Vibration resistance:</b>	According to IEC 60068-2-6: 10 ... 500 Hz: 5 g
<b>Climate resistance:</b>	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

**CERTIFICATE**


<b>REACH:</b>	REACH compliant
<b>RoHS:</b>	RoHS compliant

**OTHER**

<b>Short Description:</b>	Actuator, Ø 22.3 mm, Ø 29,5 mm, Black, round, Silver, Metal, Momentary, IP66, IP67, IP69K
<b>Housing material:</b>	Metal
<b>Wiring diagrams:</b>	



**Mounting cut-outs:**



**Dimension drawings:**

