


Actuator

51-

441.036DF





https://www.eao.com/component/51-441.036DF/en...



51-441.036DF Actuator

_	_		K I	4
г	н	U	N	1

Front dimension: 18 mm x 18 mm

Front form: Square

MOUNTING

Design: Flush

Mounting cut-out: 21 mm x 21 mm

Mounting type: Panel mounting

ELECTRICAL CHARACTERISTICS

Switching voltage and switching

current:

100 mA at 42 VAC/VDC

Contacts: 2 NO

Switching rating: 42 V @ 0,1 A

Electric strength: 2500 VAC, 50 Hz, 1 min. between all terminals and earth, according to IEC 61058-

1, part 15

Electrostatic discharge (ESD): $\leq 15 \text{ kV}$

MECHANICAL CHARACTERISTICS

Terminal: Universal terminal, 2 x 0.5 mm

Contact material: Gold

Switching action: Rest (a) - Maintained (a)

Switching system: Low-level element

Switching system: This low-level switching element was designed for switching low powers in

electronic circuits. The mechanism assures reliable switching of loads ranging from

a few $\mu A/\mu V$ up to 100 mA/ 42 VAC/DC.

Single-break momentary contact, as normally open or normally closed with 4 independent points of contact. 2 momentary contactsper switching element; combination of normally open and normally closed is possible. Special features are the long life, extremely short rebound time and stable contact resistance.

Switching positions: 2 positions

Switching angle: 90° right

Mechanical lifetime: 50 000 cycles of operation

Operating force: 1,8 ... 3,5 N

Tightening torque: Fixing nut max. 0.5 Nm

Terminal details 1: The universal terminals permit these units to be mounted on printed circuit boards

> (PCB). These terminals can also be used as soldering or plug-in terminals. For these terminals we can also supply a plug-in base which, when soldered on to

the board, enables the switch to be plugged in.

Weight: 0.017 kg

AMBIENT CONDITION

IP front protection: IP65, according to DIN EN 60529

– 25 °C ... + 55 °C Operating temperature:

– 40 °C ... + 85 °C Storage temperature:

Shock resistance: 15 g for 11 ms, as per DIN / EN 60512-4-3, DIN / EN 60068-2-27 (Single impacts,

semi-sinusoidal)

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER


Short Description: Actuator, 21 mm x 21 mm, 18 mm x 18 mm, Square, 2 NO, Rest (a) - Maintained

(a), Universal terminal, 2 x 0.5 mm, IP65, according to DIN EN 60529


Black **Housing colour:**

Standard lock: DOM 311 Hints:


Switching positions:



Wiring diagrams:




Component layouts:




A = Universal terminal (rear side) B = Plug-in terminal (rear side) C = Anti twist device D = Drilling plan

Mounting cut-outs:



Dimension drawings:



A = Solder terminal

B = Solder terminal 2.8 mm x 0.5 mm C = Universal terminal 2.0 mm x 0.5 mm