

# Actuator

51-496.025D2F





https://www.eao.com/component/51-496.025D2F/e...



# 51-496.025D2F Actuator

E	D	0	N	п
г	п	v	14	

Front dimension: 24 mm x 18 mm

Front form: Rectangular

#### **MOUNTING**

Design: Flush

Mounting cut-out: 21 mm x 27 mm

Panel mounting Mounting type:

## **ELECTRICAL CHARACTERISTICS**

Switching voltage and switching

current:

250 VAC, 5 A (ohmic)

250 VAC, 3 A (Soldering terminal) 250 VAC, 2 A (inductive, cos(phi) = 0.7) 125 VAC, 3 A (inductive, cos(phi) = 0.7) 220 VDC, 0.1 A (inductive, L:R = 30 ms) 110 VDC, 0.2 A (inductive, L:R = 30 ms) 60 VDC, 0.7 A (inductive, L:R = 30 ms) 24 VDC, 2 A (inductive, L:R = 30 ms)

Contacts: 2 NC / 2 NO

250 V @ 5 A Switching rating:

**Electrical lifetime:** 50 000 cycles of operation

Electric strength: 2500 VAC, 50 Hz, 1 min. between all terminals and earth, according to IEC 61058-

1, part 15

**Protection class:** 

Standards: According to EN/IEC 61058-1

Thermal current Ith:

The maximum current in continuous operation and at ambient temperature not

exceeding the quoted maximum values.

#### **MECHANICAL CHARACTERISTICS**

Terminal: Soldering terminal

Contact material: Gold

Switching action: Rest (a) - Momentary

**Switching system:** Snap-action switching element

Switching system: Self-cleaning, double-break snap action switching system, 1 normally closed and 1

normally open contact per element.

**Switching positions:** 2 positions

Switching angle: 42° right

**Mechanical lifetime:** 50 000 cycles of operation

**Operating force:** 1,8 ... 6 N, depending on the number of switching elements

**Tightening torque:** Fixing nut max. 0.5 Nm

Wire cross section: Snap-action switching element with tinned soldering terminals at the sides

Max. wire diameter 2 wires à 1.2 mm

Max. wire cross-section of stranded cable 1 x 1 mm<sup>2</sup>

Weight: 0.02 kg

#### **AMBIENT CONDITION**

**IP front protection:** IP65, according to DIN EN 60529

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... \, + 55 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40~^{\circ}\text{C}$  ... + 85  $^{\circ}\text{C}$ 

**Shock resistance:** 15 g for 11 ms, as per DIN / EN 60512-4-3, DIN / EN 60068-2-27 (Single impacts,

semi-sinusoidal)

Vibration resistance: 10 g at 10 Hz...1500 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN

60512-4-4, DIN EN 60068-2-6

Climate resistance: Standard condition, as per DIN EN 60068-2-30

Changing condition, as per DIN EN 60068-2-14

## **CERTIFICATE**

Approbations: CB (IEC 61058-1), CQC, CSA, DNV, ENEC (EN 61058-1), UL

Ce, UKCA, 2011 / 65 / EC (RoHS), 2014 / 30 / EU (EMC), 2014 / 35 / EU (LVD)

**REACH:** REACH compliant

RoHS: RoHS compliant

**Short Description:** 

Actuator, 21 mm x 27 mm, 24 mm x 18 mm, Rectangular, 2 NC / 2 NO, Rest (a) - Momentary, Soldering terminal, IP65, according to DIN EN 60529

Housing colour:

Black

Hints:


Standard lock: DOM 311

max. number of switching

elements:


4

Switching positions:




Wiring diagrams:

Mounting cut-outs:



Dimension drawings:



A = Solder terminal

B = Solder terminal 2.8 mm x 0.5 mm C = Universal terminal 2.0 mm x 0.5 mm