

# Actuator

704.062.518







# 704.062.518 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 35 mm Front form: Round Front bezel colour: Nature

Aluminium

#### **MOUNTING**

Front bezel material:

Flush Design:

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens colour: Green

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

Lens optics: transparent

#### **ELECTRICAL CHARACTERISTICS**


Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

#### **MECHANICAL CHARACTERISTICS**

Switching action: Maintained Mechanical lifetime: ≤3 Mil. cycles of operation 8 N Operating force: **Operating Travel:** ca.  $5.8 \text{ mm} \pm 0.2 \text{ mm}$ Weight: 0.046 kg **AMBIENT CONDITION IP Protection:** IP65 front side - 40 °C ... + 55 °C Operating temperature: – 40 °C ... + 85 °C Storage temperature: **CERTIFICATE REACH:** REACH compliant RoHS: RoHS compliant **OTHER** Actuator, Ø 30.5 mm, Ø 35 mm, Flush, Illuminated, Green, Plastic, transparent, **Short Description:** Round, Nature, Aluminium, anodised, Maintained Housing colour: Grey Plastic Housing material: Hints: Max. 3 switching elements can be clipped on The lamp block will be delivered with screw terminal The colour of anodised aluminium parts can vary due to technical production reasons max. number of switching 3 elements: Wiring diagrams:


# Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

### **Dimension drawings:**



A = Screw terminal