

Actuator

704.062.618







MECHANICAL CHARACTERISTICS

Switching action:


704.062.618 Actuator

FRONT	
Front dimension:	Ø 35 mm
Front form:	Round
Front bezel colour:	Nature
Front bezel material:	Aluminium
MOUNTING	
Design:	Flush
Mounting cut-out:	Ø 30.5 mm
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lens colour:	Blue
Lens material:	Plastic
Lens illumination:	Illuminated
Lens shape:	Flush
Lens optics:	transparent
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
	LIV 00341-1

Maintained

Mechanical lifetime: ≤3 Mil. cycles of operation 8 N Operating force: **Operating Travel:** ca. $5.8 \text{ mm} \pm 0.2 \text{ mm}$ Weight: 0.046 kg **AMBIENT CONDITION IP Protection:** IP65 front side - 40 °C ... + 55 °C Operating temperature: – 40 °C ... + 85 °C Storage temperature: **CERTIFICATE REACH:** REACH compliant RoHS: RoHS compliant **OTHER** Actuator, Ø 30.5 mm, Ø 35 mm, Flush, Illuminated, Blue, Plastic, transparent, **Short Description:** Round, Nature, Aluminium, anodised, Maintained Housing colour: Grey Plastic Housing material: Hints: Max. 3 switching elements can be clipped on The lamp block will be delivered with screw terminal The colour of anodised aluminium parts can vary due to technical production reasons max. number of switching 3 elements: Wiring diagrams:


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal