

Actuator

704.095.0





Your product:



704.095.0 Actuator

Front dimension: Ø 29 mm

Front form: Round

Front bezel colour: Nature

Front bezel material: Aluminium

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.5 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever colour: Black

Lever bar colour: Black

Lever material: plastic

Lever shape: long

ELECTRICAL CHARACTERISTICS

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1


MECHANICAL CHARACTERISTICS

Switching action: Momentary - Rest - Momentary

Switching positions: 3 positions

Switching angle:	42° left / 42° right	
Mechanical lifetime:	≤2.5 Mil. cycles of operation	
Weight:	0.035 kg	
AMBIENT CONDITION		
IP Protection:	IP65 front side	
Operating temperature:	– 40 °C + 55 °C	
Storage temperature:	– 40 °C + 85 °C	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, \varnothing 29 mm, non illuminative, Black, long, Round, Nature, Aluminium, anodised, Momentary - Rest - Momentary	
Hints:	Max. 3 switching elements can be clipped on	
max. number of switching elements:	3	
Switching positions:		
Wining diagram		
Wiring diagrams:		


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal