

Actuator

704.510.0081





https://www.eao.com/component/704.510.008l/en...

Your product:



704.510.008l Actuator

Front dimension: 35 mm x 35 mm

Front form: Square

Front bezel colour: Silver

Front bezel material: Plastic

MOUNTING

Design: Flush

Mounting cut-out: 30 mm x 30 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever colour: Black

Lever bar colour: translucent

Lever material: plastic

Lever shape: short

ELECTRICAL CHARACTERISTICS

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

MECHANICAL CHARACTERISTICS

Switching action: Rest - Maintained

Switching positions: 2 positions

Switching angle: 90° right

Mechanical lifetime: ≤2.5 Mil. cycles of operation

Weight: 0.043 kg

AMBIENT CONDITION

IP Protection: IP65 front side

Operating temperature: – 40 °C ... + 55 °C

– 40 °C ... + 85 °C Storage temperature:

CERTIFICATE

REACH compliant **REACH:**

RoHS: RoHS compliant

OTHER

Actuator, 30 mm x 30 mm, 35 mm x 35 mm, optional illuminative, Black, short, Square, Silver, Plastic, Rest - Maintained **Short Description:**


Hints: Max. 3 switching elements can be clipped on

max. number of switching


elements:

3


Switching positions:



Wiring diagrams:



Mounting cut-outs:




A = Screw terminal

B = Push-in terminal (PIT)

C = Plug-in terminal 6.3 mm x 0.8 mm D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal