

Actuator

704.632.1







704.632.1 Actuator

FRONT	
Front form:	Round
MOUNTING	
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lens illumination:	Illuminated
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
MECHANICAL CHARACTERISTICS	
Switching action:	Maintained

≤3 Mil. cycles of operation

ca. 5.8 mm ± 0.2 mm

8 N

0.009 kg

AMBIENT CONDITION

Mechanical lifetime:


Operating force:

Operating Travel:

Weight:

IP Protection:	IP65 front side
Operating temperature:	– 40 °C + 55 °C
Storage temperature:	– 40 °C + 85 °C
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, Illuminated, Round, Maintained
Housing colour:	Grey
Housing material:	Plastic
Hints:	Max. 3 switching elements can be clipped on
max. number of switching elements:	3
Wiring diagrams:	
	E~-

Mounting cut-outs:




A = Screw terminal

B = Push-in terminal (PIT)

C = Plug-in terminal 6.3 mm x 0.8 mm

D = Double plug-in terminal 6.3 mm \times 0.8

mm




A = Screw terminal

B = Push-in terminal (PIT)


C = Plug-in terminal 6.3 mm x 0.8 mm

D = Double plug-in terminal 6.3 mm x 0.8 mm


Dimension drawings:




A = Screw terminal



A = Screw terminal



A = Screw terminal



A = Screw terminal