

Indicator element

84-8001.4620





Your product:



84-8001.4620 Indicator element

UP	EKA	AT IN	G-/IN	IDICA	HON	PARI

Illumination colour: Yellow

ELECTRICAL CHARACTERISTICS

Operating voltage: 24 V DC $\pm 10 \%$

Lumi. Intensity: mcd

MECHANICAL CHARATERISTIC

Terminal: Plug-in terminal, 2.8 x 0.8 mm

Weight: 0.005 kg

AMBIENT CONDITION

IP Protection: IP40

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Indicator element, Yellow, Single-LED, 24 V DC ±10 %, Plug-in terminal, 2.8 x 0.8

mm

Kind of illlumination: Single-LED

Hints: LED and built-in resistor included, Standard version: Cable length 300 mm, Other

options on request: Customisation of cable and connectors, rear side fully sealed (IP 67), Protection degree (rear side): IP 40, upgrade to IP 67 with plug Part No. 84-

900 possible. With applications where strong vibrations occure, the plugs may become loose, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED

Wiring diagrams:

